

400 Series 403D-15G

13.2 kWm @ 1500 rpm

The Perkins® 400 Series engine family continues to set new standards in the compact engine market. Developed alongside customers to fulfill their needs in the generator set, compressor, agricultural and general industrial markets.

These ElectropaKs provide compact power, from a robust family of 3 and 4 cylinder diesel engines designed to provide economic and durable operation at prime and standby duties, hitting the key power nodes required by the power generation industry.



Emissions statement

Constant Speed Engines for use in Industrial, IOPU and ElectropaK applications: Certified against the requirements of EU Stage IIIA (Directives 97/68/EC, as last amended, for mobile applications).

Specification		
Number of cylinders	3 vertical in-line	
Bore and stroke	84 x 90 mm	3.3 x 3.5 in
Displacement	1.496 litres	91.3 in ³
Aspiration	Naturally aspirated	
Cycle	4 stroke	
Combustion system	Indirect injection	
Compression ratio	22.5:1	
Rotation	Anti-clockwise, viewed on flywheel	
Total lubricating capacity	6.0 litres	1.6 US gal
Cooling system	Water cooled	
Total coolant capacity	6.0 litres	1.6 US gal

Features and benefits

Powered by your needs

- | The 403D-15G ElectropaK is a powerful but quiet 1.5 litre naturally aspirated 3-cylinder compact package

Compact, clean, efficient power

- | Design features on the 400D range of ElectropaKs ensures clean rapid starting in all conditions whilst delivering impressive performance with low operating costs in a small, efficient package size

Lower operating costs

- Approved for operation on biodiesel* concentrations of up to 20%
- | Oil and filter changes are 500 hours, dependent on load factor
- | Engine durability and reliability, the warranty offering and ease of installation combine to drive down the cost of ownership
- | Warranties and Service Contracts
 - We provide one-year warranties for constant speed engines and two-year warranties for variable speed models, as standard. These are supported by multilevel Extended Service Contracts that can be bought additionally
 - Discover more: www.perkins.esc

Long-term power solution

- | The 400D range of ElectropaKs has been designed to fully comply with stringent EU emissions regulations, providing an emissions compliant power solution for the future

Product support

- With highly trained Perkins distributors in thousands of communities in over 180 countries, you are never far away from expert product knowledge, genuine parts and a range of advanced diagnostic technology for keeping your engine in peak condition
- | To find your local distributor: www.perkins.com/distributor

Technical information

Air inlet

- ▮ Mounted airfilter

Fuel system

- ▮ Mechanically governed cassette type fuel injection pump
- ▮ Split element fuel filter

Lubrication system

- ▮ Wet steel sump with filler and dipstick
- ▮ Spin-on full-flow lub oil filter

Cooling system

- ▮ Thermostatically-controlled system with belt driven coolant pump and pusher fan
- ▮ Mounted radiator, piping and guards

Electrical equipment

- ▮ 12 volt starter motor and 12 volt 65 amp alternator with DC output
- ▮ Oil pressure and coolant temperature switches
- ▮ 12 volt shut-off solenoid energised to run
- ▮ Glow plug cold start aid and heater/starter switch

Flywheel and housing

- ▮ High inertia flywheel to SAE J620 Size 7½ Heavy
- ▮ Flywheel housing SAE 4 Long

Mountings

- ▮ Front and rear engine mounting bracket

Optional equipment

- ▮ Parts book

Option groups

A selection of optional items is available to enable you to prepare a specification precisely matched to your needs.

Engine package weights and dimensions

Length	820 mm	32.3 in
Width	497 mm	19.6 in
Height	791 mm	31.1 in
Weight (dry)	197 kg	434 lb

Speed rpm	Type of operation	Typical generator output (Net)		Engine power			
				Gross		Net	
		kVA	kWe	kWm	hp	kWm	hp
1500	Prime power	13.1	10.4	12.2	16.4	12.0	16.0
	Standby power	14.5	11.6	13.5	18.1	13.2	17.6

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1. Derating may be required for conditions outside these; consult Perkins Engines Company Limited.

Generator powers are typical and are based on typical alternator efficiencies and a power factor (cos θ) of 0.8. Fuel specification: BS 2869: Part 2 1998 Class A2 or ASTM D975 D2.

Rating definitions: Prime power: Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours operation. Standby (maximum): Power available at variable load in the event of a main power network failure. No overload is permitted.

Percent of prime power	Fuel consumption at 1500 rpm g/kWh	Fuel consumption at 1500 rpm l/hr
Standby power	251	4.8
Prime power	248	3.6
75%	252	2.8
50%	277	2.0

POWERMAX

ADDRESS

Bab-e-Arif Apartment,
Shop no.A-59, North Karachi.

WEBSITE

www.powermaxgenerator.com

CONTACT

+923212010005

EMAIL

ajazahmedkhan@powermaxgenerator.com

info@powermaxgenerator.com

coxpower786@gmail.com

