

## 2000 Series 2206C-E13TAG3

**392 kWm @ 1500 rpm**

The 2200 range has been developed using the latest engineering techniques and builds on the strengths of the already very successful 2000 Series family. Developed from a proven heavy-duty industrial base, these products offer the superior performance and reliability required to meet today's uncompromising demands within the power generation industry.

The 2206C-E13TAG is a 6 cylinder, turbocharged air-to-air charge cooled diesel engine. Its premium features provide exceptional power to weight ratio resulting in exceptional fuel consumption.

The overall performance and reliability characteristics make this the prime choice for today's power generation industry.



Specification		
Number of cylinders	6 vertical in-line	
Bore and stroke	130 x 157 mm	5.1 x 6.1 in
Displacement	12.5 litres	763 in <sup>3</sup>
Aspiration	Turbocharged and air-to-air chargecooled	
Cycle	4 stroke	
Combustion system	Direct injection	
Compression ratio	16.3:1	
Rotation	Anti-clockwise, viewed on flywheel	
Total lubricating capacity	40 litres	10.5 US gal
Cooling system	Water-cooled	
Total coolant capacity	51.4 litres	13.6 US gal

## Features and benefits

### Economic power

- ▮ Mechanically operated unit fuel injectors with electronic control combined with carefully matched turbocharging, give excellent fuel atomisation and combustion with optimum economy
- ▮ Low emissions result from electronic control of fuel injected

### Reliable power

- ▮ Developed and tested using the latest engineering techniques and finite element analysis for high reliability, low oil usage and low wear rates
- ▮ High compression ratios ensure clean rapid starting in all conditions
- ▮ Perkins global product support is designed to enhance the customer experience of owning a Perkins powered machine. We deliver this through the quality of our distribution network, extensive global coverage and a range of Perkins supported OEM partnership options. So whether you are an end-user or an equipment manufacturer our engine expertise is essential to your success

### Compact, clean and efficient power

- ▮ Exceptional power to weight ratio and compact size give optimum power density for ease of installation and more cost effective transportation
- ▮ Designed to provide excellent service access for ease of maintenance

### Product support

- ▮ Perkins actively pursues product support excellence by ensuring our distribution network invest in their territory – strengthening relationships and providing more value to you, our customer
- ▮ Through an experienced global network of distributors and dealers, fully trained engine experts deliver total service support around the clock, 365 days a year. They have a comprehensive suite of web based tools at their fingertips covering technical information, parts identification and ordering systems, all dedicated to maximising the productivity of your engine
- ▮ Throughout the entire life of a Perkins engine, we provide access to genuine OE specification parts and service. We give 100% reassurance that you receive the very best in terms of quality for lowest possible cost .. wherever your Perkins powered machine is operating in the world

*Certified against the requirements of EU2007 Stage II (EU97/68/EC Stage II) legislation for non-road mobile machinery, powered by constant speed engines and is capable of meeting 1/2 TA Luft (1986) emissions legislation.*

## Technical information

### Air inlet

- ▮ Mounted airfilter

### Fuel system

- ▮ Mechanically actuated electronically controlled unit fuel injectors with full authority electronic control
- ▮ Governing to ISO 8528-5 class G2 with isochronous capability
- ▮ Replaceable 'Ecoplus' fuel filter elements with primary filter/water separator
- ▮ Fuel cooler

### Lubrication system

- ▮ Wet sump with filler and dipstick
- ▮ Full-flow replaceable 'Ecoplus' filter
- ▮ Oil cooler integral with filter header

### Cooling system

- ▮ Gear-driven circulating pump
- ▮ Mounted belt-driven pusher fan
- ▮ Radiator incorporating air-to-air charge cooler, (supplied loose)
- ▮ System designed for ambients up to 50°C

### Electrical equipment

- ▮ 24 volt starter motor and 24 volt 70 amp alternator with DC output
- ▮ ECM mounted on engine with wiring looms and sensors
- ▮ 3 level engine protection system

### Flywheel and housing

- ▮ High inertia flywheel to SAE J620 size 14
- ▮ SAE 1 flywheel housing

### Mountings


- ▮ Front engine mounting bracket

### Literature

- ▮ User's Handbook and Parts Manual

### Optional equipment

- ▮ 110 volt/240 volt immersion heater
- ▮ Additional speed sensor
- ▮ Temperature and pressure sensors for gauges
- ▮ Air filter rain hood
- ▮ Twin starters/facility for second starter
- ▮ Tool kit



**Engine package weights and dimensions**

Length	2410 mm	95 in
Width	1120 mm	44 in
Height	1725 mm	68 in
Weight (dry)	1478 kg	3258 lb

POWERMAX

Speed rpm	Type of operation	Typical generator output (Net)		Engine power			
				Gross		Net	
		kVA	kWe	kWm	hp	kWm	hp
1500	Prime power	400	320	368	493	349	468
	Standby power	450	360	413	554	392	526

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1, DIN 6271. Derating may be required for conditions outside these; consult Perkins Engines Company Limited.

Generator powers are typical and are based on an average alternator efficiency and a power factor (cos.  $\theta$ ) of 0.8. Fuel specification: BS 2869: Part 2 1998 Class A2 or BSEN590 or ASTM D975 Class 1D and 2D. Lubricating oil: 15W40 to API CI4.

**Rating definitions**

Prime power: Variable load. Unlimited hours usage with an average load factor of 70% of the published prime power rating over each 24 hour period. A 10% overload is available for 1 hour in every 12 hours of operation. Standby power: Variable load. Limited to 500 hours annual usage up to 300 hours of which may be continuous running. No overload is permitted.

Percent of prime power	Fuel consumption at 1500 rpm g/kWh	Fuel consumption at 1500 rpm l/hr
Standby power	202	94
110%	205	93
100%	206	85
75%	210	65
50%	218	46

# **POWERMAX**

**ADDRESS**

Bab-e-Arif Apartment,  
Shop no.A-59, North Karachi.

**WEBSITE**

[www.powermaxgenerator.com](http://www.powermaxgenerator.com)

**CONTACT #**

+923212010005

**EMAIL**

[ajazahmedkhan@powermaxgenerator.com](mailto:ajazahmedkhan@powermaxgenerator.com)

[info@powermaxgenerator.com](mailto:info@powermaxgenerator.com)

[coxpower786@gmail.com](mailto:coxpower786@gmail.com)

